

PRIVACY FENCE SLAT FOR CHAIN LINK FENCING

Since the 1990's Loxcreen (Div of M-D Building Products) has been manufacturing high quality fence slat profiles for distributors and wholesale fence manufacturers. Our unique "Dualox W" slat design, marketed under the Casa Verde brand is easily installed and manufactured in our bi-coastal manufacturing facilities located in Woodburn, OR and Brooklet, GA.

MATERIALS

This "Dualox" slat profile is produced form High Density Polyethylene (HDPE). HDPE is a versatile material commonly found in household chemical containers and cosmetic vials. HDPE has great temperature range and stays durable from -30 degrees F to over 200 degrees F. This material is resitant to extreme weather, salt water, and common outdoor pollutants.

COLOR WEATHERABILITY

We use only the best ultra violet (UV) colorants designed to retain color in the harshest of outdoor conditions. Our "Dualox" slat carries a 10 year limited warranty on color.

PRIVACY AND WIND LOAD FACTORS

The Dualox slat covers approximately 75%. Loxcreen is not responsible for fence damage resulting from insufficient structural support.

STANDARD COLORS: GREEN, REDWOOD, BEIGE, WHITE, BLACK



STANDARD HEIGHTS: 5 FT, 6 FT, 8 FT.

Other lengths availableupon special order program. actual slat length is 4" shorter than fence height.

PACKAGING

Slats are packaged in a convenient to store 2.75" x 3" carton. Each box contains 82 pcs (slats) which covers 10 feet of chain link fence. Bottom locking channels are included in each box for securing the slats in place.

SLAT TYPE "Dualox W"

SLAT WIDTH

1 1/4 "

MESH SIZE

2", 2 1/4" or 2 3/8"

WIRE GAUGE

9", 11", 11 1/2"

FENCE SLAT INSTALL ATTON



Slide locking channel horizontally through links, open end up, through the bottom row of fence links.



At the top, insert slats vertically with tapered end facing down.



Push slat through links until it "clicks" into the locking channel.

LOCKING CHANNEL



MADE IN THE USA



ISO 9001 Certified Management System

